DU10E

Carlo Gavazzi Inductive Proximity Plastic Fork Shaped NPN Normally Open Output 10mm 2m Cable

NON-CONTACT SENSORS



Component type	Inductive proximity switch
Range	Inductive Prox
Model	N/A
Alternative	CALL FOR ALTERNATIVE

The Carlo Gavazzi Inductive Proximity Sensors are a reliable and contactless solution in the detection of machinery and automation equipment. Available in a variety of styles and resistant to high level shock and vibration. Able to withstand wide temperature variations and voltage peaks of up to 200V making them ideal for high pressure and high temperature wash-down environments.

ELECTRICAL	Type of actuation	Metallic Target
	Switching distance	10 mm
	Voltage type	DC
	Rated control supply voltage Us at DC	21.6-26.4 V
	Max. output current at protected output	200 mA
	Type of switch function	Normally open contact
	Type of switching output	NPN
	Switching frequency	1000 Hz
	Type of electric connection	Cable
	Supply voltage	21.6-26.4 V
	Number of protected semiconductor outputs	1
COMMUNICATION	Type of interface	None
CONSTRUCTION	Construction type housing	Cuboid
	Material housing	Plastic
	IP rating	IP67
	Coating housing	Other
	Cascadable	No
	Compression-resistant	No
	Suitable for safety functions	No
MECHANICAL	Mechanical mounting condition for sensor	Other
DIMENSIONS	Length of sensor	45 mm
	Height of sensor	44.5 mm
	Cable length	2 m
	Weight (cable excluded)	116 g
	Width sensor	25.6 mm
ENVIRONMENT	Storage temperature	-25…70 °C

Published on 15 July 2026

DU10E

Carlo Gavazzi Inductive Proximity Plastic Fork Shaped NPN Normally Open Output 10mm 2m Cable

NON-CONTACT SENSORS

CERTIFICATES/APPROVALS

SIL according to IEC 61508	None
Explosion safety category for gas	None
Explosion safety category for dust	None

Published on 15 July 2026