FB16480

CUBIC CuFlex Flexible Copper Busbar 16mm2 Length 480mm Black and Dark Grey

FLEXIBLE BUSBAR BRAIDS

CUBIC



Component type	Busbar
Range	CuFlex
Model	N/A
Product status	Existing

NHP's Cu-flex busbars ensure a prompt and professional execution of electrical connections. The busbars are supplied ready to go. This means that you do not have to spend time on shortening, stripping the wires, making holes or complicated bends. Cu-flex is made of copper wires that are woven to a flexible busbar.

ELECTRICAL	Rated current In	90 A
	Nominal voltage	1000 V
	Rated short-time withstand current Icc	11 A
	Rated insulation voltage Ui	1000 V
	Power loss	5.3 W
CONSTRUCTION	Flexible	Yes
	Colour housing	Grey/black
	Fire resistant properties	According to UL94 V1
	Model	Flat
	Surface protection	Untreated
DIMENSIONS	Length	480 mm
	Width	20 mm
	Height	1.5 mm
	Wire/conductor size	16 mm
ENVIRONMENT	Max. operating temperature	90 °C

Published on 02 June 2026


FB16480

CUBIC CuFlex Flexible Copper Busbar 16mm2 Length 480mm Black and Dark Grey

FLEXIBLE BUSBAR BRAIDS

CUBIC

DIMENSIONAL DIAGRAM



Published on 02 June 2026