

MOLED10002A

Moflash LED100 ECO Beacon 8 LEDS STD or FLASH Mode
IP65 20 to 30V AC DC Wall or SUF Mount Lens Amber



MOFLASH
SIGNALLING



Component type	Signalling device
Range	LED Beacon
Model	N/A
Product status	Existing

The Moflash range of LED Beacons are a highly efficient and durable visual signalling solution for industrial and commercial applications. LED technology ensures a bright output, visible from a distance with a wide choice of colours, sizes, outputs, configurations, voltages, mounting options and a variety of operation modes such as flashing or rotating.

ELECTRICAL	Rated operation current I _e	0.11 A
	Nominal voltage	20-30 V
	Type of current	AC/DC
	Electricity consumption	0.11 A
COMMUNICATION	Compatible with Apple HomeKit	No
	Compatible with Google Assistant	No
	Compatible with Amazon Alexa	No
CONSTRUCTION	Colour of lamp hood	Orange
	Mounting method	Other
	Colour housing	Black
	IP rating	IP65
MECHANICAL	Suitable for ceiling mounting	Yes
PHOTOMETRIC	Lamp type	LED
	Illumination mode	Continuous light
ENVIRONMENT	Rated temperature	-25...55 °C

MOLED10002A

Moflash LED100 ECO Beacon 8 LEDS STD or FLASH Mode
IP65 20 to 30V AC DC Wall or SUF Mount Lens Amber



BEACONS

MOFLASH
SIGNALLING

DIMENSIONAL DIAGRAM

