PQFLEDPLB

Stanilite Single Point Platinum Exit Lighting LED Quickfit LED Less Bracket



Component type	Emergency luminaire
Range	Single Point Platinum Exit Lighting
Model	N/A
Alternative	PQFLEDP

The Stanilite single point Platinum exit lighting range features energy saving LED light source, efficient lithium power and fully retrofittable to previous generations of Quickfits.

ELECTRICAL	**Operating mode**	Maintained
	Nominal voltage	240 V
	Voltage type	AC
	Max. system power	3.2 W
	Viewing distance	24 m
	Nominal operation time	100000 h
	Driver type	LED
CONSTRUCTION	**With remote switch connection**	No
	With remote control	No
	Mounting method	Wall/ceiling/suspension
	With pictogram	Yes
	With light source	Yes
	Material housing	ABS
	Colour housing	White
	Material cover	Acrylic
	IP rating	IP20
PHOTOMETRIC	**Lamp type**	LED not exchangeable
	Photometric classification (C0)	D3.2
	Photometric classification	D3.2
DIMENSIONS	**Width**	72 mm
	Height/depth	214 mm
	Length	379 mm
ENVIRONMENT	**Rated ambient temperature according to IEC62722-2-1**	0…40 °C
CERTIFICATES/APPROVALS	**Compliant to AS/NZS CISPR 15**	Yes
	Compliant to AS/NZS 2293.3:2018	Yes

Published on 17 April 2026

PQFLEDPLB

Stanilite Single Point Platinum Exit Lighting LED Quickfit LED Less Bracket

CERTIFICATES/APPROVALS		
	Compliant to AS/NZS 60598.1:2017	Yes
	Compliant to AS/NZS 60598.2.22:2005	Yes

RELATED PRODUCTS

ACCESSORY



Item No: PICTOINSERTS

Required: No

Description: Stanilite Emergency Accessories Insert Picto Set

Published on 17 April 2026