

PQSVGC70030OXFFCX1A

Delta SVG/APF/Hybrid IP30 Cabinet 7x 100kVAr/A Power Modules Front Connect Orange



POWER FACTOR CORRECTION



Component type	Energy management controller
Range	TPFC
Model	N/A
Product status	Existing

The Delta Hybrid system is a modular solution that combines the APF and SVG systems to provide dedicated displacement and distortion power correction in a single cabinet. Providing a high harmonic filtering rate (>98%) for harmonics from the 2nd to the 50th order, with a fast response time (<20 ms) the hybrid serves as an all-in-one solution to boost the true power factor of an electrical network.

ELECTRICAL

Application	Power quality
Supply voltage	380-415 V
Voltage type of supply voltage	AC
Number of phases	3
Rated frequency	50-60 Hz
Rated current	700 A

CONSTRUCTION

Type of enclosure	Floor mounting
Number of module positions	7
Number of empty module positions	7
Colour	Orange
RAL-number	2000
IP rating	IP30
Suitable for outdoor set-up	No

DIMENSIONS

Width	1009.5 mm
Depth	1000.5 mm
Height	2258 mm
Weight	380 kg

PQSVGC70030OXFFCX1A

Delta SVG/APF/Hybrid IP30 Cabinet 7x 100kVar/A Power
Modules Front Connect Orange



POWER FACTOR CORRECTION



DIMENSIONAL DIAGRAM

