PSFDN1603PR

CUBIC Modular Plug In Fuse Switch PSF DN 3Pole 160A External Handle Kit R



Component type	Fuse switch disconnector
Range	Fuse Switch
Model	N/A
Alternative	CALL FOR ALTERNATIVE

The Socomec SSF standard fuse switches boast IP 30 protection on all fuse terminals in a compact yet effective design. These fuse switches feature a test position and double-break contacts per phase, allowing the safe isolation of AC or DC circuits as well as the added short circuit protection offered by DIN/BS type HRC fuses.

ELECTRICAL	Rated current	160 A
	Max. rated operation voltage Ue AC	690 V
	Max. rated operation voltage Ue DC	440 V
	Rated permanent current at AC-21, 400 V	160 A
	Rated permanent current at AC-23, 400 V	160 A
	Rated operation current Ie at DC-21, 220 V	160 A
	Rated operation current Ie at DC-22, 220 V	160 A
	Short time withstand current Icw, 1 sec	50 kA
	Rated impulse withstand voltage Uimp	8 kV
	Rated insulation voltage Ui	750 V
	Rated operation power at AC-23, 400 V	80 kW
CONSTRUCTION	Degree of protection (IP), front side	IP30
MECHANICAL	Suitable for fuses	NH00
	Mechanical life (service cycles)	10000 cycles

Published on 21 July 2026

PSFDN1603PR

CUBIC Modular Plug In Fuse Switch PSF DN 3Pole 160A External Handle Kit R

DIMENSIONAL DIAGRAM



Published on 21 July 2026