

RZ7FSI3EA40

Sprecher and Schuh RZ7 Timer Relay On Delay Pulse
Generator 346 to 440V AC Supply 1CO 0.05 to 1min



Component type	Timer relay
Range	RZ7
Model	N/A
Alternative	CALL FOR ALTERNATIVE

The Sprecher + Schuh range of RZ7-FS and FE electronic timing relays is a reliable, economical and flexible solution for control and timing application processes. Available in single and multi-function timers, with various timing modes and contact outputs, and timing ranges from 0.05s and up to 300 hours. Optional width sizes including 17.5mm and 22.5mm.

ELECTRICAL

Voltage type for actuating	AC/DC
Rated control supply voltage U_s at DC	24-48 V
Rated control supply voltage U_s at AC 60HZ	346-440 V
Rated control supply voltage U_s at AC 50HZ	346-440 V
Number of outputs, delayed, change-over contact	1
Rated operation current I_e at DC-13, 24 V	1 A
Rated operation current I_e at AC-15, 250 V	3 A
Type of electric connection	Screw connection
Function delay-on energization	Yes
Function delay on de-energization	No
Function floating contact on energization	No
Function floating contact on de-energization	No
Function star-delta	No
Function pulse shaping	No
Function flashing, starting with pause, fixed time	No
Function flashing, starting with pulse, fixed time	No
Clock function, starting with pause, variable	Yes
Clock function, starting with pulse, variable	Yes
Time range	0.05-60 s
Time setting accuracy	5 %
Power supply reset time	50 ms
Power consumption	0.5 VA
Electrical lifespan (control contacts)	200000 c (contacts)
Real power	0.5 W

RZ7FSI3EA40

Sprecher and Schuh RZ7 Timer Relay On Delay Pulse
Generator 346 to 440V AC Supply 1CO 0.05 to 1min



CONSTRUCTION

Degree of protection (IP), front side	IP30
Degree of protection (IP), rear side	IP20

MECHANICAL

Suitable for DIN rail (top hat rail) mounting	Yes
Mechanical lifetime (control contacts)	3.0E7 c (contacts)
Max. shock acceleration	50 g
Max. vibration acceleration	4 m/s²
Max. vibration frequency, operational	100 Hz


DIMENSIONS

Height	78.8 mm
Depth	109 mm
Width	22.5 mm


ENVIRONMENT

Operating temperature	-25...45 °C
-----------------------	-------------

DIMENSIONAL DIAGRAM



RZ7-FS (1 C/O)



RZ7-FS (2 C/O)