140GK6F3D30

Allen-Bradley 140G MCCB K Frame 70kA 3P 300A Adjustable Thermal Magnetic



Component type	Power switching circuit breaker
Range	Moulded Case Circuit Breaker
Model	N/A
Product status	Existing

The Allen Bradley motor protection circuit breakers offer a reliable solution with both short-circuit and overload protection for individual motor loads with high interrupt ratings for 2 and 3 pole devices. Ideal for motor starting and motor protection applications. Connecting modules are available and have been combination short-circuit tested with the Allen Bradley 100-E contactors.

ELECTRICAL	Rated current In	300 A
	Number of poles	3
	Max. rated operation voltage Ue AC	690 V
	Rated ultimate short-circuit breaking capacity Icu at 415 V, 50 Hz	70 kA
	Type of protection trip unit	Thermal/magnetic release
	Trip curve	Adj. thermal, adj. magnetic
	Frame size rating	400 A
	Long time overload protection adjustment range	210-300 A
	Instantaneous protection adjustment range	1500-3000 A
	Integrated earth fault protection	No
	Rated frequency	50-60 Hz
	Rated insulation voltage Ui	1000 V
	Suitable for isolation	Yes
	Rated short circuit breaking capacity, Icu 690V AC	40 kA
	Rated short circuit breaking capacity, Ics 690V AC	40 kA
	Rated impulse withstand voltage Uimp	8 kV
	Motor drive integrated	No
	Reverse connection of supply possible	Yes
	Electrical life at Un, In (service cycles)	7000 cycles
	Complete device with protection unit	No
	Power loss	40.8 W
CONSTRUCTION	Air circuit breaker (withdrawable)	No
MECHANICAL	DIN rail (top hat rail) mounting optional	No
	Mechanical life (service cycles)	20000 cycles

140GK6F3D30

Allen-Bradley 140G MCCB K Frame 70kA 3P 300A Adjustable Thermal Magnetic


DIMENSIONS	Height	205 mm
	Width	139.5 mm
	Pole connection pitch	46.5 mm
	Built-in depth	103.5 mm
	Depth (toggle included)	139 mm
	Weight	3.25 kg
ENVIRONMENT	Rated surrounding temperature without derating	40 °C
	Maximum operating temperature	75 °C
	Storage temperature	-40…80 °C
	Max. altitude before derating	2000 m


Published on 14 October 2026

140GK6F3D30

Allen-Bradley 140G MCCB K Frame 70kA 3P 300A Adjustable Thermal Magnetic

DIMENSIONAL DIAGRAM





Published on 14 October 2026