

140MTCAFA20

Allen-Bradley 140MT Auxiliary Contact with 2NO Contacts Front Mount



MOTOR PROTECTION



Allen-Bradley

Component type	Auxiliary contact block
Range	140MT
Model	N/A
Product status	Existing

The Allen-Bradley Bulletin 140MT Motor Protection Circuit Breakers provide magnetic short-circuit and thermal overload protection up to 40A. Assembled starters can be applied without additional branch circuit protection. Motor circuit protectors are applied with a separate overload relay for three-component starters, available in two frame sizes.



ELECTRICAL

Number of contacts as normally open contact	2
Rated insulation voltage U_i	250 V
Rated operation current I_e at AC-15, 24 V	4 A
Rated operation current I_e at AC-15, 120 V	3 A
Rated operation current I_e at AC-15, 240 V	1.5 A
Rated operation current I_e at DC-13, 24 V	1.2 A
Rated operation current I_e at DC-13, 125 V	0.22 A
Rated operation current I_e at DC-13, 250 V	0.11 A

CONSTRUCTION

Mounting method	Front fastening
-----------------	-----------------

RELATED PRODUCTS

ACCESSORY



Item No: 140MCPE23

Required: No

Description: Allen-Bradley 140M Connecting Link 140MC to 100C 09 to 23