194LE124531

Allen-Bradley 194L Cam Switch 1Pole 12A Panel Mount 60 Degree Step 1 2 3 4 5 6



Component type	Off-load switch
Range	194L
Model	N/A
Product status	Existing

The Allen-Bradley 194L range of rotary cam switches are designed for use in control and load switching based applications rated from 12A to 40A. Modular in design and available with a range of frame sizes, faceplate and switch body designs for various switching configurations. Optional accessories include shaft extensions and enclosures for various applications.

ELECTRICAL	Number of poles	1
	Rated uninterrupted current Iu	12 A
	Rated operation current Ie at AC-15, 230 V	5 A
	Rated operation current Ie at AC-15, 400 V	3 A
	Rated operation current Ie at AC-22a, 690 V	12 A
	Rated operation current Ie at AC-22a, 220-500 V	12 A
	Rated operation current Ie at AC-21a, 690V	12 A
	Rated operation current Ie at AC-1, 690V	12 A
	Ithe, thermal current (enclosed)	12 A
	Ith, thermal current (open)	16 A
	Number of auxiliary contacts as normally closed contact	0
	Number of auxiliary contacts as normally open contact	0
	Number of auxiliary contacts as change-over contact	0
	Type of electrical connection of main circuit	Screw connection
CONSTRUCTION	Model	Other
	Mounting method	Front mounting
	Material housing	Plastic
	Wire/conductor size, rigid cable	1-2.5 mm²
	Wire/conductor size, flex cable	1-2.5 mm²
	Degree of protection (IP), front side	IP20
	Suitable for front mounting	Yes
	Suitable for distribution board installation	No
	Complete device in housing	No
MECHANICAL	With zero (off) position	No


Published on 21 July 2026


194LE124531

Allen-Bradley 194L Cam Switch 1Pole 12A Panel Mount 60 Degree Step 1 2 3 4 5 6

MECHANICAL	Mechanical life (service cycles)	1000000 cycles
	Number of switch positions	6
	With retraction in 0-position	No
DIMENSIONS	Depth	64 mm
	Width	42 mm
	Height	42 mm
ENVIRONMENT	Operating temperature	-25…60 °C

DIMENSIONAL DIAGRAM





Cat. No.	L				
	No. of Contacts				
	1 – 2	3 – 4	5 – 6	7 – 8	9 – 10
194L-E12/16...	67.5 (2-21/32)	77.5 (3-3/64)	87.5 (3-7/16)	97.5 (3-27/32)	107.5 (4-15/64)
194L-E20/25...	69 (2-23/32)	81.5 (3-7/32)	94 (3-45/64)	106.5 (4-3/16)	119 (4-11/16)

Published on 21 July 2026