194RN601753

Allen-Bradley 194R Load Break Switch UL 194R 60A 3Pole



Component type	Switch disconnector
Range	194R Loadbreak
Model	N/A
Product status	Existing

ELECTRICAL	**Rated uninterrupted current Iu**	60 A
	Number of poles	3
	Type of control element	Long turning handle
	Type of electrical connection of main circuit	Screw connection
	Number of auxiliary contacts as normally closed contact	0
	Number of auxiliary contacts as normally open contact	0
	Motor drive integrated	No
	Voltage release optional	No
CONSTRUCTION	**Device construction**	Complete device in housing
	Degree of protection (IP), front side	IP20
	Version as main switch	Yes
	Version as maintenance-/service switch	No
	Version as safety switch	No
	Version as emergency stop installation	No
	Version as reversing switch	No
	Number of switches	1
	Suitable for front mounting 4-hole	No
	Suitable for distribution board installation	Yes
	Interlockable	No
DIMENSIONS	**Height**	248 mm
	Width	197 mm
	Depth	111 mm
	Weight	1.14 kg
	Connectable conductor cross section	2.5-25 mm²

Published on 30 September 2026

ENVIRONMENT	Rated surrounding temperature without derating	60 °C
	Storage temperature	-40…65 °C
	Allowable relative humidity	95 %