20AC022F0AYNANC0

Allen-Bradley PowerFlex 70 VSD 400V Flange Mount 22A 11kW ND or 15A 7.5kW HD

LARGE DRIVES



Component type	Frequency converter =< 1 kV
Range	PowerFlex 70
Model	N/A
Product status	Phased Out

The Allen-Bradley PowerFlex® 70 AC Drives are a compact packaged motor control solution with operator interface designed for space saving, simplicity and reliability. Featuring integration into an architecture and configured to provide a solution for various application needs.

ELECTRICAL	Number of phases input	3
	Nominal input voltage	415 V
	Nominal output power AC	11 kW
	Nominal output current I2N	22 A
	kW rating, normal duty	11 kW
	kW rating, heavy duty	7.5 kW
	Number of phases output	3
	Mains frequency	50 Hz
	Dynamic braking transistor	Yes
	Control characteristic	PID
	EMC-version	Yes
	Mains voltage	400 V
COMMUNICATION	Number of HW-interfaces RS-485	2
	Supporting protocol for EtherNet/IP	Yes
	Supporting protocol for Modbus	Yes
	Supporting protocol for DeviceNet	Yes
	Supporting protocol for TCP/IP	Yes
	Supporting protocol for PROFIBUS	Yes
	Supporting protocol for CAN	Yes
	Number of HW-interfaces RS-232	2
	Number of HW-interfaces USB	2
CONSTRUCTION	Suitable for safety functions	Yes
	Number of digital inputs	6
	Number of digital outputs	2
	Number of analogue inputs	2
	Number of analogue outputs	1

Published on 05 November 2026

20AC022F0AYNANC0

Allen-Bradley PowerFlex 70 VSD 400V Flange Mount 22A 11kW ND or 15A 7.5kW HD

LARGE DRIVES

CONSTRUCTION	Frame size	D
	IP rating	IP20
	Relative symmetric net voltage tolerance	10 %
	With control element	Yes
	Application in industrial area permitted	Yes
	Application in domestic- and commercial area permitted	Yes
	Integrated breaking resistance	No
	Degree of protection (NEMA)	1
DIMENSIONS	Height	350 mm
	Width	219.9 mm
	Depth	210.7 mm
	Weight	9.13 kg

Published on 05 November 2026