20G11ND040AA0NNNNN

Allen-Bradley PowerFlex 755 VSD 480V IP20 ND 40A 30HP or 34A 25HP Frame 3

LARGE DRIVES



Component type	Frequency converter =< 1 kV
Range	PowerFlex 755
Model	N/A
Alternative	CALL FOR ALTERNATIVE

Allen-Bradley PowerFlex 755 AC Drives are a simple and high-performance motor control application, providing a variety of solutions including pumps, fans, and conveyors. Featuring a standard built-in Ethernet/IP port, making it ideal for applications requiring flexibility, connectivity, control, advanced communications, hardware. and safety options.

ELECTRICAL	Number of phases input	3
	Nominal input voltage	480 V
	Nominal output power AC	22 kW
	Nominal output current I2N	40 A
	kW rating, normal duty	22 kW
	kW rating, heavy duty	18 kW
	Dynamic braking transistor	Yes
	Control characteristic	PID
	EMC-version	Yes
COMMUNICATION	Integrated motion function	No
CONSTRUCTION	Suitable for safety functions	Yes
	Contains keypad	No
	Frame size	3
	IP rating	IP20
	Degree of protection (NEMA)	Other
DIMENSIONS	Height	454 mm
	Width	190 mm
	Depth	212 mm
	Weight	12 kg
ENVIRONMENT	Operating temperature	-20…60 °C
	Storage temperature	-40…70 °C

Published on 29 May 2026