20G11RC2P1AA0NNNNN

Allen-Bradley PowerFlex 755 VSD 400V IP20 ND 2.1A 0.75kW or HD 1.5A 0.37kW Frame 1

LARGE DRIVES



Component type	Frequency converter =< 1 kV
Range	PowerFlex 755
Model	N/A
Alternative	20G11RC2P1JA0NNNNN

Allen-Bradley PowerFlex 755 AC Drives are a simple and high-performance motor control application, providing a variety of solutions including pumps, fans, and conveyors. Featuring a standard built-in Ethernet/IP port, making it ideal for applications requiring flexibility, connectivity, control, advanced communications, hardware. and safety options.

ELECTRICAL	Number of phases input	3
	Nominal input voltage	400 V
	Nominal output power AC	0.75 kW
	Nominal output current I2N	2.1 A
	kW rating, normal duty	0.75 kW
	kW rating, heavy duty	0.37 kW
	Dynamic braking transistor	Yes
	Control characteristic	PID
	EMC-version	Yes
COMMUNICATION	Integrated motion function	No
CONSTRUCTION	Suitable for safety functions	Yes
	Contains keypad	No
	Frame size	1
	IP rating	IP20
DIMENSIONS	Height	400 mm
	Width	190 mm
	Depth	211.1 mm
	Weight	6 kg
ENVIRONMENT	Operating temperature	-20…60 °C
	Storage temperature	-40…70 °C

Published on 12 August 2026