

20G11RD5P0AA0NNNNN

Allen-Bradley PowerFlex 755 VSD 480V IP20 ND 5A 3HP or HD
3.4A 2HP Frame 1



LARGE DRIVES



Allen-Bradley



Component type	Frequency converter =< 1 kV
Range	PowerFlex 755
Model	N/A
Alternative	CALL FOR ALTERNATIVE

Allen-Bradley PowerFlex 755 AC Drives are a simple and high-performance motor control application, providing a variety of solutions including pumps, fans, and conveyors. Featuring a standard built-in Ethernet/IP port, making it ideal for applications requiring flexibility, connectivity, control, advanced communications, hardware. and safety options.

ELECTRICAL

Number of phases input	3
Nominal input voltage	480 V
Nominal output power AC	2.2 kW
Nominal output current I2N	5 A
kW rating, normal duty	2.2 kW
kW rating, heavy duty	1.5 kW
Dynamic braking transistor	Yes
Control characteristic	PID
EMC-version	Yes

COMMUNICATION

Integrated motion function	No
Suitable for safety functions	Yes

CONSTRUCTION

Contains keypad	No
Frame size	1
IP rating	IP20

DIMENSIONS

Height	400 mm
Width	190 mm
Depth	211.1 mm
Weight	6 kg

ENVIRONMENT

Operating temperature	-20...60 °C
Storage temperature	-40...70 °C