## 20G1ANC260JA0NNNNN

Allen-Bradley PowerFlex 755 VSD 400V IP20 ND 260A 132kW or HD 205A 110kW Frame 6





Component type	Frequency converter =< 1 kV
Range	PowerFlex 755
Model	N/A
Product status	Existing

The Allen-Bradley PowerFlex 755 AC Drives are an simple and high performance motor control application, providing a variety of solutions including pumps, fans and conveyors. Featuring standard built in Ethernet/IP port making it ideal for applications requiring flexibility, connectivity, control, advanced communications, hardware and safety options.

ELECTRICAL	Number of phases input	3
	Nominal input voltage	400 V
	Nominal output power AC	132 kW
	Nominal output current I2N	260 A
	kW rating, normal duty	132 kW
	kW rating, heavy duty	110 kW
	Dynamic braking transistor	Yes
	Control characteristic	PID
	EMC-version	Yes
COMMUNICATION	Integrated motion function	No
CONSTRUCTION	Suitable for safety functions	Yes
	Contains keypad	No
	Frame size	6
	IP rating	IP20
	Degree of protection (NEMA)	Other
DIMENSIONS	Height	665.5 mm
	Width	308 mm
	Depth	346.4 mm
	Weight	48 kg
ENVIRONMENT	Operating temperature	-2060 °C
	Storage temperature	-4070 °C