

20G21GD014JA0NNNNN

Allen-Bradley PowerFlex 755TS VSD 480V IP54 ND 14A 10HP or HD 11A 7.5HP Frame 2



LARGE DRIVES



Allen-Bradley



Component type	Frequency converter =< 1 kV
Range	PowerFlex 755T
Model	N/A
Product status	Existing

The Allen-Bradley PowerFlex 755T range of variable speed drives are an extension to the PowerFlex 750 drive portfolio providing solutions for harmonic mitigation and regeneration applications. Fitted with TotalFORCE technology they deliver high performance motor control, adaptive control of torque, velocity, position and predictive analytics on the drives health.

ELECTRICAL

Number of phases input	3
Nominal input voltage	480 V
Nominal output power AC	7.4 kW
Nominal output current I2N	14 A
kW rating, normal duty	7.5 kW
kW rating, heavy duty	5.5 kW
Dynamic braking transistor	Yes
Control characteristic	PID
EMC-version	Yes

COMMUNICATION

Integrated motion function	No
Suitable for safety functions	Yes

CONSTRUCTION

Contains keypad	Yes
Frame size	2
IP rating	IP54
Degree of protection (NEMA)	12

DIMENSIONS

Height	543.2 mm
Width	216.5 mm
Depth	225.6 mm
Weight	8 kg

ENVIRONMENT

Operating temperature	-20...60 °C
Storage temperature	-40...70 °C

20G21GD014JA0NNNNN

Allen-Bradley PowerFlex 755TS VSD 480V IP54 ND 14A 10HP or
HD 11A 7.5HP Frame 2




LARGE DRIVES



Allen-Bradley

DIMENSIONAL DIAGRAM



Dimensions are in millimeters and (inches).
Weights are in kilograms and (pounds).

Frame	A	B	C	D	E	Weight, kg (lb)
2	215.3 (8.48)	543.2 (21.39)	222.2 (8.75)	100.0 (3.94)	528.2 (20.80)	7.8 (17.2)
3	268.0 (10.55)	551.0 (21.69)	220.1 (8.67)	158.0 (6.22)	533.0 (20.98)	11.8 (26.1)
4	300.0 (11.81)	571.0 (22.48)	220.1 (8.67)	194.0 (7.64)	553.0 (21.77)	13.6 (30.0)
5	348.0 (13.70)	647.0 (25.47)	220.1 (8.67)	238.0 (9.37)	629.0 (24.76)	20.4 (45.0)