26016120

Socomec SLB Load Break Switch Body, 6P 1200A

LOAD BREAK SWITCHES



Component type	Switch disconnector
Range	SLB
Model	N/A
Product status	Existing

Compact switching solutions from 125A up to 5000A, the SLB range of load break switches are a proven, reliable design. Severe load duty categories (AC-22 and AC-23) are well suited to the arduous switching of motors, main switch isolation and disconnection of other loads.

ELECTRICAL	Max. rated operation voltage Ue AC	500 V
	Rated permanent current at AC-21, 400 V	1200 A
	Rated uninterrupted current Iu	1200 A
	Number of poles	6
	Rated operation power at AC-23, 400 V	710 kW
	Rated short-time withstand current Icw	65 kA
	Rated insulation voltage Ui	1000 V
	Type of control element	Other
	Rated operating voltage	400-500 V
	Rated permanent current at AC-23, 400 V	1200 A
	Switching power at 400 V	750 kW
	Conditioned rated short-circuit current Iq	50 kA
	Number of auxiliary contacts as normally closed contact	0
	Number of auxiliary contacts as normally open contact	0
	Number of auxiliary contacts as change-over contact	0
	Motor drive optional	No
	Motor drive integrated	No
	Voltage release optional	No
CONSTRUCTION	Device construction	Built-in device fixed built-in technique
	Colour control element	Other
	Degree of protection (IP), front side	IP65
	Version as main switch	Yes
	Version as maintenance-/service switch	Yes
	Version as safety switch	Yes

26016120

Socomec SLB Load Break Switch Body, 6P 1200A

LOAD BREAK SWITCHES

CONSTRUCTION	Version as emergency stop installation	Yes
	Version as reversing switch	No
	Number of switches	1
	Suitable for front mounting 4-hole	No
	Suitable for front mounting centre	No
	Suitable for distribution board installation	No
	Interlockable	Yes
DIMENSIONS	Height	100 mm
	Width	100 mm
	Depth	100 mm