3PS63D3NE01P

PROCONECT 3PS63 Socket Outlet, 3P+N+E+2p, 90A (AC23 63A) 440V AC

ISOLATING PLUGS

PROCONECT®



Component type	Round socket/plug for high currents
Range	3PS
Model	N/A
Product status	Existing

Recognised as a leading provider of industrial plugs and sockets for mining, food processing, commercial, rail and marine industries, the 3PS isolating plugs and sockets from Proconect are available in five sizes: 30A, 50A, 90A, 150A and 250A, tested against IEC 60309-1 standard. The isolating plugs and sockets eliminate the need for a switch and ensures power is safely available when required.

ELECTRICAL	Amperage	90 A
	Voltage	380-440 V
	Contact configuration	3P+N+E+2P
CONSTRUCTION	Construction type	Outlet
	Material insulation body	Polyamide (PA)
	Contact material	Other
	Material screw	Stainless steel
	IP rating	IP66
MECHANICAL	Nominal tightening torque	4 Nm
DIMENSIONS	Length	114.5 mm
	Weight	0.64 kg
ENVIRONMENT	Operating temperature	-30…60 °C

Published on 31 August 2026


3PS63D3NE01P

PROCONECT 3PS63 Socket Outlet, 3P+N+E+2p, 90A (AC23 63A) 440V AC

ISOLATING PLUGS

PROCONECT®

DIMENSIONAL DIAGRAM



Series	A	B	C θ	D	E	F	G	H θ	Kg
3PS16	13	71	57	72	97.5	48	48	4.5	0.24
3PS32	16.5	77	69	82	107.5	55	55	4.5	0.38
3PS63	25	89.5	80	100	123.5	66	66	5.5	0.64
3PS125	24	122	99.5	129.2	145	81	81	6	1.50
3PS200	36	122	116	146	177	98	98	6.8	2.40

RELATED PRODUCTS


ACCESSORY



Item No: 3PS6G
Required: No
Description: PROCONECT 3PS63 Handle - Straight, suits 9-29mm cable



Item No: 3PS6GFP
Required: No
Description: PROCONECT 3PS63 Handle - Straight, suits 28-38mm cable, M50 gland



Item No: 3PS6LB
Required: No
Description: PROCONECT 3PS63 Incline Sleeve - Angled (30 degrees)



Item No: 3PS6PC
Required: No
Description: PROCONECT 3PS63 Appliance Inlet, Plug Cap

Item No: 3PS6WAS
Required: No
Description: PROCONECT 3PS63 Wall Box - Angled (30 degrees), M40x1.5mm Entry

Published on 31 August 2026