440RE23193

AB 440R MSR Expansion Module 24VDC 1NC/2NC-IN 4NO-SFTY 2NC-AUX 1S AM DELAY

SAFETY LOGIC



Component type	Device for monitoring of safety-related circuits
Range	MSR
Model	N/A
Product status	Existing

The Allen-Bradley Single-Function and Specialty Relays are designed for small or single-zone safety applications. Ideal for safe speed control (MSR57), back EMF monitor (MSR55), safety control circuits involving light curtains, laser scanners, safety mats, interlock switches, guard locking interlocks, two-hand controls, safety edges, enabling devices and E-stop push buttons.

ELECTRICAL	Voltage type for actuating	DC
	Control supply voltage Us at DC	24 V
	Safety category according to EN ISO 13849-1	4
	Number of outputs, safety related, undelayed, with contact	4
CONSTRUCTION	Rail mounting possible	Yes
	IP rating	IP40
	Degree of protection (IP), terminals	IP20
MECHANICAL	Max. shock acceleration	10 g
	Max. vibration displacement (Pk-Pk)	0.35 mm
	Max. vibration frequency, operational	55 Hz
DIMENSIONS	Width	22.5 mm
	Height	99 mm
	Depth	114.5 mm
	Weight	0.22 kg
ENVIRONMENT	Rated temperature	-5…55 °C

Published on 04 August 2026