

800H6HZ4R

Allen-Bradley 800H Enclosure Rosite Glass Polyester 6 Holes 3 4 Inch Conduit Entry



PUSHBUTTON AND PILOT LIGHTS



Allen-Bradley



Component type	Control circuit devices combination in enclosure
Range	800T/H Pushbutton
Model	N/A
Product status	Existing

The Allen-Bradley 800T/H range of 30.5mm mount operators are designed and constructed to perform in the most demanding industrial environments. The range includes pushbuttons, selector switches, emergency stops, pilot lights. Available in both metal and plastic types with a modular design allowing for easy selection, configuration and assembly of components to form the operator control device.

CONSTRUCTION

Number of push buttons	6
Number of key switches	6
Number of selector switches	6
Number of mushroom-shaped push-buttons	6
Colour housing cover	Grey
Material housing	Other

MECHANICAL

Max. vibration acceleration	10 m/s ²
Max. vibration frequency, operational	2000 Hz
Max. shock acceleration	100 g

DIMENSIONS

Height	377.8 mm
Width	96.8 mm
Depth	100.8 mm

ENVIRONMENT

Operating temperature	-40-55
-----------------------	--------

800H6HZ4R

Allen-Bradley 800H Enclosure Rosite Glass Polyester 6 Holes 3
4 Inch Conduit Entry




PUSHBUTTON AND PILOT LIGHTS



Allen-Bradley

DIMENSIONAL DIAGRAM



Type 4/4X/13 Rosite Glass Polyester
Watertight, Oiltight, Corrosion Resistant Enclosure