# CA7PA10

**S+S CA7 Auxiliary Contact with 1NO  Contact Side Mount**

CONTACTORS




| | |
|---|---|
| **Component type** | Auxiliary contact block |
| **Range** | CA7 |
| **Model** | N/A |
| **Product status** | Existing |

The Sprecher + Schuh CA7 contactors are the ideal solution for reliable and durable electrical components. It is a modern and flexible IEC power contactor for DOL starting needs with up to 100A AC3 and wide range selection covering from 4kW up to 63kW (400V).

| | | |
|---|---|---|
| **ELECTRICAL** | Number of contacts as normally open contact | 1 |
| | Rated insulation voltage Ui | 690 V |
| | Rated operation current Ie at AC-15, 24 V | 6 A |
| | Rated operation current Ie at AC-15, 120 V | 6 A |
| | Rated operation current Ie at AC-15, 240 V | 5 A |
| | Rated operation current Ie at AC-15, 400 V | 3 A |
| | Rated operation current Ie at DC-12, 24 V | 6 A |
| | Rated operation current Ie at DC-12, 110 V | 1 A |
| | Rated operation current Ie at DC-12, 220 V | 0.5 A |
| | Rated operation current Ie at DC-13, 24 V | 5 A |
| | Rated operation current Ie at DC-13, 110 V | 0.68 A |
| | Rated operation current Ie at DC-13, 220 V | 0.32 A |
| | Min. contact rating current | 10 mA |
| | Min. contact rating voltage | 17 V |
| | Rated operation current Ie at AC-15, 230 V | 5.5 A |
| **CONSTRUCTION** | Mounting method | Side mounting |





Published on 17 November 2026