CA7PV20

S+S CA7 Auxiliary Contact with 2NO Contacts

CONTACTORS



Component type	Auxiliary contact block
Range	CA7
Model	N/A
Product status	Existing

The Sprecher + Schuh CA7 contactors are the ideal solution for reliable and durable electrical components. It is a modern and flexible IEC power contactor for DOL starting needs with up to 100A AC3 and wide range selection covering from 4kW up to 63kW (400V).

ELECTRICAL	Number of contacts as normally open contact	2
	Rated insulation voltage Ui	690 V
	Rated operation current Ie at AC-15, 24 V	6 A
	Rated operation current Ie at AC-15, 120 V	6 A
	Rated operation current Ie at AC-15, 240 V	5 A
	Rated operation current Ie at AC-15, 400 V	3 A
	Rated operation current Ie at DC-12, 24 V	12 A
	Rated operation current Ie at DC-12, 110 V	3.5 A
	Rated operation current Ie at DC-12, 220 V	0.55 A
	Rated operation current Ie at DC-13, 24 V	5 A
	Rated operation current Ie at DC-13, 110 V	1.2 A
	Rated operation current Ie at DC-13, 220 V	0.6 A
	Min. contact rating current	5 mA
	Min. contact rating voltage	17 V
	Rated operation current Ie at AC-15, 230 V	5.5 A
CONSTRUCTION	Mounting method	Top mounting

Published on 18 June 2026