CA91060EI11120WKIT

S+S CA9 Contactor Kit 630kW 3Pole 100 to 250VAC and VDC Electronic Coil 1NO 1NC Contact Auxiliary

CONTACTORS



Component type	Power contactor, AC switching
Range	CA9
Model	N/A
Product status	Existing

The Sprecher + Schuh CA9 contactors are designed with a smaller footprint and are ideal for harsh environments such as steel mills, rock quarries, mines or for large power applications where a sturdy, durable contactor is required. Combining the basic functionality of the CA7 series and the rugged performance demanded in this larger horsepower range, they are guaranteed to increase productivity.

ELECTRICAL	Number of normally open contacts as main contact	3
	Number of normally closed contacts as main contact	0
	Rated operation current Ie at AC-3, 400 V	1060 A
	Rated operation power at AC-3, 400 V	630 kW
	Rated operation current Ie at AC-1, 400 V	1650 A
	Max. rated operation voltage Ue AC	1000 V
	Voltage type for actuating	AC/DC
	Rated control supply voltage Us at AC 50HZ	100-250 V
	Rated control supply voltage Us at DC	100-250 V
	Number of auxiliary contacts as normally open contact	1
	Number of auxiliary contacts as normally closed contact	1
	Rated operation current Ie at AC-3, 690 V	970 A
	Rated operation power at AC-3, 690 V	1060 kW
	Rated operation current Ie at AC-3, 1000 V	400 A
	Rated operation power at AC-3, 1000 V	600 kW
	Rated control supply voltage Us at AC 60HZ	100-250 V
	Power consumption, AC coil pickup	2450 VA
	Power consumption, AC coil hold-in	48 VA
	Power consumption, DC coil pickup	2290 W
	Power consumption, DC coil hold-in	20.5 W
	Type of electrical connection of main circuit	Bolt connection
CONSTRUCTION	IP rating	IP00
	Mounting method	Screw mounting
DIMENSIONS	Height	392 mm

Published on 02 October 2026

CA91060EI11120WKIT

S+S CA9 Contactor Kit 630kW 3Pole 100 to 250VAC and VDC Electronic Coil 1NO 1NC Contact Auxiliary

CONTACTORS

DIMENSIONS	Width	438 mm
	Depth	244 mm
	Weight	35 kg

Published on 02 October 2026