


CA91161148WL

S+S CA9 Contactor 55kW 3Pole 48 to 130VAC and VDC Coil
1NO 1NC Contact Auxiliary with Lugs



CONTACTORS

sprecher+schuh



Component type	Power contactor, AC switching
Range	CA9
Model	N/A
Product status	Existing

The Sprecher + Schuh CA9 contactors are designed with a smaller footprint and are ideal for harsh environments such as steel mills, rock quarries, mines or for large power applications where a sturdy, durable contactor is required. Combining the basic functionality of the CA7 series and the rugged performance demanded in this larger horsepower range, they are guaranteed to increase productivity.

ELECTRICAL

Number of normally open contacts as main contact	3
Number of normally closed contacts as main contact	0
Rated operation current I_e at AC-3, 400 V	116 A
Rated operation power at AC-3, 400 V	55 kW
Rated operation current I_e at AC-1, 400 V	160 A
Max. rated operation voltage U_e AC	1000 V
Voltage type for actuating	AC/DC
Rated control supply voltage U_s at AC 50HZ	48-130 V
Rated control supply voltage U_s at DC	48-130 V
Number of auxiliary contacts as normally open contact	1
Number of auxiliary contacts as normally closed contact	1
Rated operation current I_e at AC-3, 690 V	66 A
Rated operation power at AC-3, 690 V	63 kW
Rated operation current I_e at AC-3, 1000 V	46 A
Rated operation power at AC-3, 1000 V	55 kW
Rated operation power at AC-4, 400 V	45 kW
Rated control supply voltage U_s at AC 60HZ	48-130 V
Power consumption, AC coil pickup	170 VA
Power consumption, AC coil hold-in	4 VA
Power consumption, DC coil pickup	130 W
Power consumption, DC coil hold-in	2.5 W
Type of electrical connection of main circuit	Cable clamp
Rated operation current I_e at AC-4, 400 V	84 A
IP rating	IP00

CONSTRUCTION

CA91161148WL

S+S CA9 Contactor 55kW 3Pole 48 to 130VAC and VDC Coil
1NO 1NC Contact Auxiliary with Lugs



CONTACTORS


sprecher+schuh

CONSTRUCTION	Mounting method	Screw mounting
DIMENSIONS	Height	150 mm
	Width	90 mm
	Depth	142.5 mm
	Weight	1.75 kg

DIMENSIONAL DIAGRAM

Series CA9-116...146-_-L (Contactors/Reversing Contactors)

Dimensions are in millimeters (inches). Dimensions not intended for manufacturing purposes.



RELATED PRODUCTS

ACCESSORY



Item No: CA9A116

Required: No

Description: S+S CA9 Main Contact Set for CA9116



Item No: CA9M100

Required: No

Description: S+S CA9 Mechanical Interlock



Item No: CA9CL146

Required: No

Description: S+S CA9 Terminal Lug Kit for CA9 116 to 146A



Item No: CA9M400

Required: No

Description: S+S CA9 Mechanical Interlock

CA91161148WL

S+S CA9 Contactor 55kW 3Pole 48 to 130VAC and VDC Coil
1NO 1NC Contact Auxiliary with Lugs




CONTACTORS

sprecher+schuh

RELATED PRODUCTS


ACCESSORY



Item No: CA9MR146

Required: No

Description: S+S CA9 Mounting Plate for 116 and 146A Reversing Contactor



Item No: CA9MRS146

Required: No


Description: S+S CA9 Mounting Plate for 116 and 146A Reversing Starter



Item No: CA9PW146

Required: No


Description: S+S CA9 Reversing Starter Power Connection Links for CA9 116 to 146A



Item No: CA9PWD146

Required: No

Description: S+S CA9 Star Delta Starter Power Connection Links CA9 116 to 146A



Item No: CA9PWD190

Required: No

Description: S+S CA9 Star Delta Starter Power Connection Links CA9 190 to 205A



Item No: CA9PWY146

Required: No


Description: S+S CA9 Star Point Shorting Link for CA9 116 to 146A



Item No: CA9S111

Required: No

Description: S+S CA9 Auxiliary Contact with 1NO Contact and 1NC Contact Inside Position for CA9 116 and 370



Item No: CA9S1B01

Required: No

Description: S+S CA9 Auxiliary Contact with 1NC Contact Low Power Inside Position for CA9 116 and 370



Item No: CA9S1B10

Required: No


Description: S+S CA9 Auxiliary Contact with 1NO Contact Low Power Inside Position for CA9 116 and 370



Item No: CA9S211

Required: No

Description: S+S CA9 Auxiliary Contact with 1NO Contact and 1NC Contact Outside Position for CA9 116 and 370



Item No: CA9TE146

Required: No

Description: S+S CA9 Terminal Enlargement for CA9 116 to 146A



Item No: CA9TG913

Required: No

Description: S+S CA9 Coil for CA9 116 24 to 60VAC and VDC



Item No: CA9TG914

Required: No

Description: S+S CA9 Coil for CA9 116 48 to 130VAC and VDC



Item No: CA9TG915

Required: No

Description: S+S CA9 Coil for CA9 116 100 to 250VAC and VDC



Item No: CA9TG916

Required: No

Description: S+S CA9 Coil for CA9 116 250 to 500VAC and VDC



Item No: CA9TS146L

Required: No

Description: S+S CA9 Terminal Shrouds for CA9 116 to 146A