CA914611120WL

S+S CA9 Contactor 75kW 3Pole 100 to 250VAC and VDC Coil 1NO 1NC Contact Auxiliary with Lugs

CONTACTORS



Component type	Power contactor, AC switching
Range	CA9
Model	N/A
Product status	Existing

The Sprecher + Schuh CA9 contactors are designed with a smaller footprint and are ideal for harsh environments such as steel mills, rock quarries, mines or for large power applications where a sturdy, durable contactor is required. Combining the basic functionality of the CA7 series and the rugged performance demanded in this larger horsepower range, they are guaranteed to increase productivity.

ELECTRICAL	Number of normally open contacts as main contact	3
	Number of normally closed contacts as main contact	0
	Rated operation current Ie at AC-3, 400 V	146 A
	Rated operation power at AC-3, 400 V	75 kW
	Rated operation current Ie at AC-1, 400 V	225 A
	Max. rated operation voltage Ue AC	1000 V
	Voltage type for actuating	AC/DC
	Rated control supply voltage Us at AC 50HZ	100-250 V
	Rated control supply voltage Us at DC	100-250 V
	Number of auxiliary contacts as normally open contact	1
	Number of auxiliary contacts as normally closed contact	1
	Rated operation current Ie at AC-3, 690 V	93 A
	Rated operation power at AC-3, 690 V	90 kW
	Rated operation current Ie at AC-3, 1000 V	60 A
	Rated operation power at AC-3, 1000 V	75 kW
	Rated operation power at AC-4, 400 V	55 kW
	Rated control supply voltage Us at AC 60HZ	100-250 V
	Power consumption, AC coil pickup	130 VA
	Power consumption, AC coil hold-in	6 VA
	Power consumption, DC coil pickup	135 W
	Power consumption, DC coil hold-in	5 W
	Type of electrical connection of main circuit	Cable clamp
	Rated operation current Ie at AC-4, 400 V	103 A
CONSTRUCTION	IP rating	IP00

Published on 03 November 2026

CA914611120WL

S+S CA9 Contactor 75kW 3Pole 100 to 250VAC and VDC Coil 1NO 1NC Contact Auxiliary with Lugs


CONTACTORS

CONSTRUCTION	**Mounting method**	Screw mounting
DIMENSIONS	**Height**	150 mm
	Width	90 mm
	Depth	126 mm
	Weight	1.75 kg

DIMENSIONAL DIAGRAM

Series CA9-116…146-_-L (Contactors/Reversing Contactors)

Dimensions are in millimeters (inches). Dimensions not intended for manufacturing purposes.



RELATED PRODUCTS

ACCESSORY



Item No: CA9A146
Required: No
Description: S+S CA9 Main Contact Set for CA9146



Item No: CA9M400
Required: No
Description: S+S CA9 Mechanical Interlock



Item No: CA9CL146
Required: No
Description: S+S CA9 Terminal Lug Kit for CA9 116 to 146A

Item No: CA9MR146
Required: No
Description: S+S CA9 Mounting Plate for 116 and 146A Reversing Contactor

Published on 03 November 2026

CA914611120WL

S+S CA9 Contactor 75kW 3Pole 100 to 250VAC and VDC Coil 1NO 1NC Contact Auxiliary with Lugs

CONTACTORS

RELATED PRODUCTS

ACCESSORY

Item No: CA9MRS146
Required: No
Description: S+S CA9 Mounting Plate for 116 and 146A Reversing Starter




Item No: CA9PW146
Required: No
Description: S+S CA9 Reversing Starter Power Connection Links for CA9 116 to 146A

Item No: CA9PWD146
Required: No
Description: S+S CA9 Star Delta Starter Power Connection Links CA9 116 to 146A

Item No: CA9PWD190
Required: No
Description: S+S CA9 Star Delta Starter Power Connection Links CA9 190 to 205A



Item No: CA9PWY146
Required: No
Description: S+S CA9 Star Point Shorting Link for CA9 116 to 146A



Item No: CA9TE146
Required: No
Description: S+S CA9 Terminal Enlargement for CA9 116 to 146A



Item No: CA9TG901
Required: No
Description: S+S CA9 Coil for CA9 146 24 to 60VAC and VDC



Item No: CA9TG902
Required: No
Description: S+S CA9 Coil for CA9 146 48 to 130VAC and VDC



Item No: CA9TG903
Required: No
Description: S+S CA9 Coil for CA9 146 100 to 250VAC and VDC



Item No: CA9TG904
Required: No
Description: S+S CA9 Coil for CA9 146 250 to 500VAC and VDC



Item No: CA9TS146L
Required: No
Description: S+S CA9 Terminal Shrouds for CA9 116 to 146A

Published on 03 November 2026