CA91461124W

S+S CA9 Contactor 75kW 3Pole 24 to 60VAC and VDC Coil 1NO 1NC Contact Auxiliary

CONTACTORS



Component type	Power contactor, AC switching
Range	CA9
Model	N/A
Product status	Existing

The Sprecher + Schuh CA9 contactors are designed with a smaller footprint and are ideal for harsh environments such as steel mills, rock quarries, mines or for large power applications where a sturdy, durable contactor is required. Combining the basic functionality of the CA7 series and the rugged performance demanded in this larger horsepower range, they are guaranteed to increase productivity.

ELECTRICAL	Number of normally open contacts as main contact	3
	Number of normally closed contacts as main contact	0
	Rated operation current Ie at AC-3, 400 V	146 A
	Rated operation power at AC-3, 400 V	75 kW
	Rated operation current Ie at AC-1, 400 V	225 A
	Max. rated operation voltage Ue AC	1000 V
	Voltage type for actuating	AC/DC
	Rated control supply voltage Us at AC 50HZ	24-60 V
	Rated control supply voltage Us at DC	24-60 V
	Number of auxiliary contacts as normally open contact	1
	Number of auxiliary contacts as normally closed contact	1
	Rated operation current Ie at AC-3, 690 V	93 A
	Rated operation power at AC-3, 690 V	90 kW
	Rated operation current Ie at AC-3, 1000 V	60 A
	Rated operation power at AC-3, 1000 V	75 kW
	Rated operation power at AC-4, 400 V	55 kW
	Rated control supply voltage Us at AC 60HZ	24-60 V
	Power consumption, AC coil pickup	225 VA
	Power consumption, AC coil hold-in	5.5 VA
	Power consumption, DC coil pickup	210 W
	Power consumption, DC coil hold-in	2.5 W
	Type of electrical connection of main circuit	Bolt connection
	Rated operation current Ie at AC-4, 400 V	103 A
CONSTRUCTION	IP rating	IP00

Published on 01 October 2026

CA91461124W

S+S CA9 Contactor 75kW 3Pole 24 to 60VAC and VDC Coil 1NO 1NC Contact Auxiliary

CONTACTORS

CONSTRUCTION	**Mounting method**	Screw mounting
DIMENSIONS	**Height**	150 mm
	Width	90 mm
	Depth	126 mm
	Weight	1.5 kg

Published on 01 October 2026