CA9400EI1124WKIT

S+S CA9 Contactor Kit 220kW 3Pole 24 to 60VDC Electronic Coil 1NO 1NC Contact Auxiliary

CONTACTORS



Component type	Power contactor, AC switching
Range	CA9
Model	N/A
Product status	Existing

The Sprecher + Schuh CA9 contactors are designed with a smaller footprint and are ideal for harsh environments such as steel mills, rock quarries, mines or for large power applications where a sturdy, durable contactor is required. Combining the basic functionality of the CA7 series and the rugged performance demanded in this larger horsepower range, they are guaranteed to increase productivity.

ELECTRICAL	Number of normally open contacts as main contact	3
	Number of normally closed contacts as main contact	0
	Rated operation current Ie at AC-3, 400 V	400 A
	Rated operation power at AC-3, 400 V	220 kW
	Rated operation current Ie at AC-1, 400 V	600 A
	Max. rated operation voltage Ue AC	1000 V
	Voltage type for actuating	DC
	Rated control supply voltage Us at DC	24-60 V
	Number of auxiliary contacts as normally open contact	1
	Number of auxiliary contacts as normally closed contact	1
	Rated operation current Ie at AC-3, 690 V	350 A
	Rated operation power at AC-3, 690 V	315 kW
	Rated operation current Ie at AC-3, 1000 V	155 A
	Rated operation power at AC-3, 1000 V	220 kW
	Rated operation power at AC-4, 400 V	160 kW
	Power consumption, DC coil pickup	900 W
	Power consumption, DC coil hold-in	5 W
	Type of electrical connection of main circuit	Bolt connection
	Rated operation current Ie at AC-4, 400 V	307 A
CONSTRUCTION	IP rating	IP00
	Mounting method	Screw mounting
DIMENSIONS	Height	268 mm
	Width	186 mm

Published on 01 October 2026

CA9400EI1124WKIT

S+S CA9 Contactor Kit 220kW 3Pole 24 to 60VDC Electronic Coil 1NO 1NC Contact Auxiliary

CONTACTORS

DIMENSIONS

Depth	216 mm
Weight	12 kg

DIMENSIONAL DIAGRAM

Series CA9-400-EI…460-EI (Contactors/Reversing Contactors with PLC Interface)

Dimensions are in millimeters (inches). Dimensions not intended for manufacturing purposes.



Published on 01 October 2026