CA9S411

S+S CA9 Auxiliary Contact with 1NO Contact and 1NC Contact Outside Position for CA9 400 and 2650

CONTACTORS



Component type	Auxiliary contact block
Range	CA9
Model	N/A
Product status	Existing

The Sprecher + Schuh CA9 contactors are designed with a smaller footprint and are ideal for harsh environments such as steel mills, rock quarries, mines or for large power applications where a sturdy, durable contactor is required. Combining the basic functionality of the CA7 series and the rugged performance demanded in this larger horsepower range, they are guaranteed to increase productivity.

ELECTRICAL

Number of contacts as normally open contact	1
Number of contacts as normally closed contact	1
Rated insulation voltage Ui	690 V
Rated operation current Ie at AC-15, 24 V	6 A
Rated operation current Ie at AC-15, 120 V	6 A
Rated operation current Ie at AC-15, 240 V	4 A
Rated operation current Ie at AC-15, 400 V	3 A
Rated operation current Ie at DC-13, 24 V	6 A
Rated operation current Ie at DC-13, 110 V	0.55 A
Rated operation current Ie at DC-13, 220 V	0.3 A
Min. contact rating current	50 mA
Min. contact rating voltage	12 V
Rated operation current Ie at AC-15, 230 V	4 A

Published on 31 May 2026