


CAS72305C240VAC

S+S CAS7 Safety Contactor 11kW 3Pole 240VAC Coil 5NC
Contact Auxiliary



Component type	Power contactor, AC switching
Range	CAS7
Model	N/A
Alternative	CALL FOR ALTERNATIVE

The Sprecher + Schuh CAS7 Safety Contactors provide reliable and efficient performance in industrial environments where safety is a priority. The high-quality materials and advanced technologies ensure a long lifespan and reduced maintenance costs. Designed with high switching capacity and low power consumption making they are ideal for demanding environments.

ELECTRICAL

Number of normally open contacts as main contact	3
Number of normally closed contacts as main contact	0
Rated operation current I_e at AC-3, 400 V	23 A
Rated operation power at AC-3, 400 V	11 kW
Rated operation current I_e at AC-1, 400 V	32 A
Max. rated operation voltage U_e AC	690 V
Voltage type for actuating	AC
Control supply voltage U_s at AC 50HZ	240 V
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as normally closed contact	5
Rated operation current I_e at AC-3, 690 V	12 A
Rated operation power at AC-3, 690 V	10 kW
Rated operation power at AC-4, 400 V	4 kW
Control supply voltage U_s at AC 60HZ	277 V
Power consumption, AC coil pickup	75 VA
Power consumption, AC coil hold-in	9.5 VA
Type of electrical connection of main circuit	Screw connection
Rated operation current I_e at AC-4, 400 V	9 A

CONSTRUCTION

IP rating	IP20
Mounting method	DIN-rail/screw

DIMENSIONS

Height	81 mm
Width	45 mm
Depth	119.5 mm
Weight	0.45 kg


CAS72305C240VAC

S+S CAS7 Safety Contactor 11kW 3Pole 240VAC Coil 5NC
Contact Auxiliary



DIMENSIONAL DIAGRAM

Dimensions are in millimeters. Dimensions are not intended for manufacturing purposes.



Type	a	b	c	c1	c2	c3	ød	d1	d2
CAS 7 - 9...CAS 7 - 23	45	81	119.5	114.5	6	4.5	2 x 4.5	60	35 ¹⁾
CAS 7 - 30...CAS 7 - 37	45	81	136.5	131.6	6.5	4.5	2 x 4.5	60	35 ¹⁾
CAS 7 - 43	54	81	139.5	134.6	6.5	5	2 x 4.5	60	45 ¹⁾
CAS 7 - 60...CAS 7 - 85	72	122	156	150.5	8.5	5.5	4 x 5.4	100	55 ¹⁾

Accessories

Contactor with ...

		mm
Auxiliary contact block, side-mounted	1 or 2 pole	a + 9
Solid-state timing module (100-ETA)	on coil connection side	b + 24
Solid-state timing module (100-ETB / 100-ETY)	on coil connection side	b + 24
Mechanical interlock	side-mounted	a + 9
Interface	on coil connection side	b + 9
Suppressor module	on coil connection side	b + 3
Marking with:	sheets of labels	+ 0
	marking sheets with cover	+ 0
	label holder for V4/V5	+ 5.5
	label holder for V7	+ 5.5