

CEL3160MK

NHP Panelboard Accessory Isolator Switch Kit for TemBreak Pro 160A 3Pole suits NC Chassis



ELECTRICAL ENGINEERING PRODUCTS



Component type	Switch disconnector
Range	Panelboard General Accessories
Model	N/A
Product status	Existing

NHP Panelboards offer a wide range of high-quality accessories that are specifically designed, verified, and tested to ensure compliance with AS/NZS 61439.

ELECTRICAL

Max. rated operation voltage Ue AC	690 V
Rated uninterrupted current Iu	160 A
Number of poles	3
Frequency	50/60 Hz
Rated insulation voltage Ui	690 V
Rated impulse withstand voltage Uimp	8 kV
Electrical life at Un, In (service cycles)	6000 cycles
Type of control element	Toggle
Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
Motor drive integrated	No
Voltage release optional	No

CONSTRUCTION

Colour control element	Black
Version as main switch	Yes
Version as safety switch	No
Version as reversing switch	No
Number of switches	1
Suitable for front mounting 4-hole	Yes
Suitable for front mounting centre	No
Suitable for distribution board installation	Yes
Interlockable	Yes

MECHANICAL

Mechanical life (service cycles)	18000 cycles
Height	165 mm

DIMENSIONS

CEL3160MK

NHP Panelboard Accessory Isolator Switch Kit for TemBreak
Pro 160A 3Pole suits NC Chassis



ELECTRICAL ENGINEERING PRODUCTS


DIMENSIONS

Width	105 mm
Depth	95 mm
Weight	1.5 kg

ENVIRONMENT

Rated surrounding temperature without derating	70 °C
Storage temperature	-10...70 °C
Allowable relative humidity	95 %
Max. altitude before derating	2000 m

DIMENSIONAL DIAGRAM



CEL3160MK

NHP Panelboard Accessory Isolator Switch Kit for TemBreak Pro 160A 3Pole suits NC Chassis



ELECTRICAL ENGINEERING PRODUCTS

RELATED PRODUCTS

ACCESSORY



Item No: T2AX00LML3STA

Required: No

Description: Terasaki TemBreak PRO Auxiliary Switch for A and P Models 1 CO Contact General Type



Item No: T2BA25L3SH

Required: No

Description: Terasaki TemBreak PRO Interpole Barriers for A250/P250/ZS250 Qty 2



Item No: T2CF25L3SLEP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Long Style with Barrier for 3P A250 and P250 MCCB Qty 2



Item No: T2CF25L3SLHP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Long Style for 3P A250 and P250 MCCB Qty 1



Item No: T2CF25L3SLNGA

Required: No

Description: Terasaki TemBreak 2 Terminal Cover Front Connect 3P Narrow E250/S250SJ/ SN Lite



Item No: T2CF25L3SSHP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Short Style for 3P A250 and P250 MCCB Qty 1



Item No: T2CF25L3SWHP

Required: No

Description: Terasaki TemBreak PRO Terminal Cover CF Wide Style for 3P A250 and P250 MCCB Qty 1



Item No: T2FB25L3SH

Required: No

Description: Terasaki TemBreak PRO Straight Extension Bars 3P A/P/B/ZS250 MCCB Qty 3



Item No: T2FB25L3WH

Required: No


Description: Terasaki TemBreak PRO Flanged Extension Bars 3P A/P/B/ZS250 MCCB Qty 3



Item No: T2FW25LS3A

Required: No

Description: Terasaki TemBreak PRO Tunnel Terminal fits 35 to 120mm2 for A250/P250 Qty 6



Item No: T2HL25L

Required: No

Description: Terasaki TemBreak PRO Non Captive Toggle Lock 5 x 16.5mm Slot for A160/ A250/P160/P250



Item No: T2SH00LA20T

Required: No

Description: Terasaki TemBreak PRO Shunt Trip for A/P Models 230-240V AC



Item No: T2UV00LA20NT

Required: No

Description: Terasaki TemBreak PRO Undervoltage Trip Instantaneous for A/P Models 230 to 240V AC

