

ELBPM803P

NHP ELB Enclosed Load Break Switch, IP 65 Polycarbonate
Grey, 3 Pole 80A



ENCLOSED ISOLATORS

socomec
Innovative Power Solutions



Component type	Switch disconnecter
Range	ELB
Model	N/A
Product status	Phased Out

Socomec enclosed load break (ELB) switches range from 315A up to 800A and utilise IP66 powder-coated grey (RAL 7035) mild steel enclosures, suitable for indoor installations requiring chemical resistance and mechanical performance. The spacious enclosure allows for easy connection to Socomec's 3 pole load break switch, and comes with earth terminals, switch terminal cover, and shrouds.

ELECTRICAL

Rated uninterrupted current I _u	80 A
Number of poles	3
Rated operation power at AC-23, 400 V	37 kW
Rated operation current I _e at AC-23a, 400 V	80 A

CONSTRUCTION

Material housing	Plastic
Colour control element	Other
Degree of protection (IP), front side	IP65

DIMENSIONS

Height	210 mm
Width	125.5 mm
Depth	92 mm

ELBPM803P

NHP ELB Enclosed Load Break Switch, IP 65 Polycarbonate
Grey, 3 Pole 80A



ENCLOSED ISOLATORS

socomec
Innovative Power Solutions

DIMENSIONAL DIAGRAM

