ISOC332RCDPG

NHP ISO Switched Socket Outlet - RCD, 3 Round Pins 32A 250V AC, with Base, GY

ISO
INDUSTRIAL PLUGS AND SOCKETS



Component type	Socket outlet according to AS/NZS 3123
Range	ISO
Model	N/A
Product status	Existing

The often overlooked essentials that are always indispensable. Choose from NHP's range of 400+ industrial, isolating and high-current plugs, sockets and switches available for a wide breadth of applications.

ELECTRICAL	Nominal voltage	250 V
	Rated current	32 A
	RCD rating	30 mA
	Number of phases	1
	With neutral conductor contact	Yes
	With switch	Yes
	With earth leakage switch	Yes
	M rating	M180
CONSTRUCTION	Material	Plastic
	Colour	Grey
	Type of cover	Hinged lid
	Number of active pins (round)	3
	With base	Yes
	IP rating	IP66
DIMENSIONS	Base depth	63 mm
	Conductor cross section solid (solid, stranded)	4-16 mm²
	Height	198 mm
	Width	198 mm


Published on 29 June 2026

ISOC332RCDPG

NHP ISO Switched Socket Outlet - RCD, 3 Round Pins 32A 250V AC, with Base, GY

ISO
INDUSTRIAL PLUGS AND SOCKETS

DIMENSIONAL DIAGRAM



Published on 29 June 2026