MBP2400A3P

Mersen DIN Panel Mount Fuse Disconnectors 400A suits Size 2

PANELBOARDS
MODULAR

Component type	Fuse switch disconnector
Range	DIN Fuse Disconnect
Model	N/A
Product status	Phased Out

The Mersen DIN Fuse Disconnects are compact and reliable devices that combine switch functionality with high protection level of fuses. They are suitable for IEC low voltage systems and accept various classes of NH power fuses. They are easy to install and operate, with service entrance capability and CE mark.

ELECTRICAL	**Rated current**	400 A
	Max. rated operation voltage Ue AC	690 V
	Max. rated operation voltage Ue DC	440 V
	Rated impulse withstand voltage Uimp	12 kV
	Rated insulation voltage Ui	1000 V
CONSTRUCTION	**Degree of protection (IP), front side**	IP20
MECHANICAL	**Suitable for fuses**	NH2
DIMENSIONS	**Height**	251 mm
	Width	205 mm
	Depth	130 mm

RELATED PRODUCTS

ACCESSORY



Item No: MBBCS13P
Required: No
Description: Mersen DIN Base Mount Cable Shroud suits Size 1 3Pole



Item No: MBBCS23P
Required: No
Description: Mersen DIN Base Mount Cable Shroud suits Size 2 3Pole



Item No: MBCC1
Required: No
Description: Mersen DIN Wedge Clamp Size 1 Single Each



Item No: MBCC2
Required: No
Description: Mersen DIN Wedge Clamp Size 2 Single Each

Published on 21 July 2026

MBP2400A3P

Mersen DIN Panel Mount Fuse Disconnectors 400A suits Size 2

PANELBOARDS

MODULAR

RELATED PRODUCTS

ACCESSORY



Item No: MBCC3

Required: No

Description: Mersen DIN Wedge Clamp Size 3 Single Each

Item No: MBPSW

Required: No

Description: Mersen DIN Pilot Switch Lid Position Size 000 and 00 and 2 and 3 Fuse Disconnect