

MOD6325

NHP MOD6 Miniature Circuit Breaker 6kA 3Pole 25A C Curve



MOD6

MINIATURE CIRCUIT BREAKERS



Component type	Miniature circuit breaker (MCB)
Range	MOD6 MCB
Model	N/A
Alternative	MD6M325

NHP's MOD6 range of miniature circuit breakers offers cost effective solutions while providing core electrical protection, designed to detect and trip on overload and short circuit currents. These MCBs are available with a 6kA short circuit rating, with current ratings from 6-63A in 1P, 2P or 3P in C trip curve.

ELECTRICAL

Rated current	25 A
Number of poles (total)	3
Trip curve	C
Rated voltage	415 V
Frequency	50-60 Hz
Voltage type	AC/DC
Service voltage U_b , AC	12 V
Rated short-circuit breaking capacity I_{cn} according to AS/NZS 60898 at 230 VAC	6 kA
Rated short-circuit breaking capacity I_{cn} according to AS/NZS 60898 at 400 VAC	6 kA
Max. rated operation voltage U_e	440 V
Rated insulation voltage U_i	440 V
Rated impulse withstand voltage U_{imp}	6 kV

CONSTRUCTION

Number of protected poles	3
IP rating	IP40

MECHANICAL

Connectable conductor cross section solid-core	1-25 mm ²
Connectable conductor cross section multi-wired	1-25 mm ²

DIMENSIONS

Height	86 mm
Width	54 mm
Depth	76 mm
Width in number of modular spacings	3
Weight	0.36 kg

ENVIRONMENT

Pollution degree	3
------------------	---

MOD6325

NHP MOD6 Miniature Circuit Breaker 6kA 3Pole 25A C Curve



MOD6

MINIATURE CIRCUIT BREAKERS

ENVIRONMENT

Rated surrounding temperature without derating

30 °C

Rated temperature

-25...55 °C

DIMENSIONAL DIAGRAM

