
MPLA330PHJ72AA

Allen-Bradley Kinetix MPL Servo Motor 230VAC 5000 RPM 4.18Nm Incremental Encoder No Brake Keyed

SERVO MOTORS AND CABLES



Component type	Electric servomotor
Range	MP
Model	N/A
Product status	Discontinued

The Allen-Bradley MP-Series™ Low Inertia (MPL) Servo Motors are a compact, brushless high torque motor ideal for the most demanding complex motion systems. Available in nine frame sizes to suit any application.

ELECTRICAL	Voltage class AC	200 V
COMMUNICATION	Feedback type	2000 line incremental encoder
	Feedback resolution	2000 pulses/rev
CONSTRUCTION	With brake	No
	Magnet stack (length)	76.2 mm
	Magnet stack (number of magnets)	30
	IP rating	IP50
MECHANICAL	Rotational speed	5000 1/min
	Max. torque	11.1 Nm
	Torque	4.18 Nm
	Max. shock acceleration	20 g
	Max. vibration frequency, operational	2000 Hz
	Max. vibration acceleration	2.5 m/s²
DIMENSIONS	Weight	4600 g
ENVIRONMENT	Operating temperature	0…40 °C
	Allowable relative humidity	5-95 %

Published on 08 August 2026