NWP24

NHP Loadcentre Weatherproof 24 Way DIN-T Surface Mounted

ELECTRICAL ENGINEERING PRODUCTS



Component type	Small distribution board
Range	NWP
Model	N/A
Product status	Existing

ELECTRICAL	Rated current In	63 A
	Number of outgoing ways	24
	Number of poles, 18mm pitch	24
	Max. rated operation voltage Ue AC	415 V
	Rated insulation voltage Ui	500 V
	Neutral terminal block	Yes
	Neutral bar rated current	63 A
	Earthing terminal block	Yes
CONSTRUCTION	Spare DIN equipment space (poles)	24
	DIN-rail	Yes
	Number of rows	2
	Material housing	Plastic
	Colour	Other
	IP rating	IP65
	Type of cover	Door
	Transparent cover/door	Yes
	With lock	No
	Mounting method	Surface mounted (plaster)
MECHANICAL	Impact strength	IK10
DIMENSIONS	Width in number of modular spacings	24
	Height	435 mm
	Width	320 mm
	Depth	155 mm


Published on 12 June 2026


NWP24

NHP Loadcentre Weatherproof 24 Way DIN-T Surface Mounted

ELECTRICAL ENGINEERING PRODUCTS

DIMENSIONAL DIAGRAM





Published on 12 June 2026