

PBLVRF4F5WM

Stanilite Nexus RF Platinum Batten 4ft IP66 Vandalproof Anti-ligature IK10



Stanilite®

Component type	Emergency luminaire
Range	Nexus RF Platinum Batten
Model	N/A
Product status	New Item

The Stanilite NexusRF Platinum batten range features an energy saving LED light source, efficient lithium power and is retrofittable to previous T8 profile installations.



ELECTRICAL	Nominal voltage	240 V
	Voltage type	AC
	Max. system power	1 W
	Nominal operation time	75000 h
COMMUNICATION	Monitoring equipment	Radio frequency (RF)
	With remote switch connection	No
	With remote control	No
	Mounting method	Wall surface mounted / ceiling surface mounting
CONSTRUCTION	With pictogram	No
	With light source	Yes
	Material housing	Aluminium die-cast
	Colour housing	Grey
	Material cover	Polycarbonate (PC)
	IP rating	IP66
MECHANICAL	Impact strength	IK10
PHOTOMETRIC	Lamp type	LED not exchangeable
	Photometric classification (C0)	D32
	Photometric classification	C32
DIMENSIONS	Width	140 mm
	Length	1308 mm
CERTIFICATES/APPROVALS	Compliant to AS/NZS CISPR 15	Yes
	Compliant to AS/NZS 60598.1:2017	Yes
	Compliant to AS/NZS 60598.2.22:2005	Yes