PLSNXSLED

Stanilite Nexus LX Signature Exit Lighting LED Edgelit Surface

Stanilite®

Component type	Emergency luminaire
Range	Nexus RF Signature Exit Lighting
Model	N/A
Alternative	PLSNXSLEDP

ELECTRICAL	**Operating mode**	Maintained
	Nominal voltage	240 V
	Voltage type	AC
	Max. system power	2.71 W
	Viewing distance	24 m
	Nominal operation time	100000 h
	Driver type	LED
COMMUNICATION	**Monitoring equipment**	Cable system monitoring
CONSTRUCTION	**With remote switch connection**	No
	With remote control	No
	Mounting method	Ceiling surface mounting
	With pictogram	Yes
	With light source	Yes
	Material housing	Plastic
	Colour housing	White
	Material cover	Plastic, opal
	IP rating	IP20
PHOTOMETRIC	**Lamp type**	LED exchangeable
DIMENSIONS	**Width**	79 mm
	Height/depth	220 mm
	Length	375.5 mm
CERTIFICATES/APPROVALS	**Compliant to AS/NZS CISPR 15**	Yes
	Compliant to AS/NZS 2293.3:2018	Yes
	Compliant to AS/NZS 60598.1:2017	Yes
	Compliant to AS/NZS 60598.2.22:2005	Yes

Published on 26 March 2026

PLSNXSLED

Stanilite Nexus LX Signature Exit Lighting LED Edgelit Surface

DIMENSIONAL DIAGRAM

Published on 26 March 2026