
PMB01CM24

Carlo Gavazzi Timer Relay 11Pin Multifunction 24VDC and 24-240VAC Supply 1CO 0.1Sec-100Hour

TIME DELAY RELAYS



Component type	Timer relay
Range	Timer Relays
Model	N/A
Alternative	NO ALTERNATIVE ITEM

The Carlo Gavazzi Timers are ideal in a wide range of applications in automation, such as motor control centres, packaging machinery, HVAC equipment, control panels and process control systems. The range offers solutions for various functions, mountings, and output type.

ELECTRICAL

Voltage type for actuating	AC
Rated control supply voltage Us at DC	24 V
Rated control supply voltage Us at AC 60HZ	24-240 V
Rated control supply voltage Us at AC 50HZ	24-240 V
Number of outputs, delayed, change-over contact	1
Rated operation current Ie at DC-12, 24 V	0.2 A
Rated operation current Ie at DC-13, 24 V	2.5 A
Rated operation current Ie at AC-15, 250 V	2.5 A
Type of electric connection	Screw connection
Function delay-on energization	No
Function delay on de-energization	No
Function floating contact on energization	No
Function floating contact on de-energization	No
Function star-delta	No
Function pulse shaping	No
Function flashing, starting with pause, fixed time	No
Function flashing, starting with pulse, fixed time	No
Clock function, starting with pause, variable	Yes
Clock function, starting with pulse, variable	Yes
Time range	0.1-360000 s
Time setting accuracy	5 %
Power supply reset time	50 ms
Power consumption	0.5 VA
Electrical lifespan (control contacts)	200000 c (contacts)

Published on 12 May 2026


PMB01CM24

Carlo Gavazzi Timer Relay 11Pin Multifunction 24VDC and 24-240VAC Supply 1CO 0.1Sec-100Hour

TIME DELAY RELAYS

MECHANICAL	Suitable for DIN rail (top hat rail) mounting	Yes
	Mechanical lifetime (control contacts)	3.0E7 c (contacts)
	Max. shock acceleration	50 g
	Max. vibration acceleration	4 m/s²
	Max. vibration frequency, operational	100 Hz
DIMENSIONS	Height	80 mm
	Depth	109 mm
	Width	22.5 mm
ENVIRONMENT	Operating temperature	-25…45 °C

DIMENSIONAL DIAGRAM



Published on 12 May 2026