SCLWEM20LS

Stanilite Single Point Signature Circular Lighting LED Ip65 EM 2000 Lumens



Component type	Emergency luminaire
Range	Single Point Signature Circular Lighting
Model	N/A
Alternative	PCWEMLEDS

ELECTRICAL	**Operating mode**	Maintained
	Nominal voltage	240 V
	Voltage type	AC
	Max. system power	1 W
	Nominal operation time	100000 h
	Driver type	LED
CONSTRUCTION	**With remote switch connection**	No
	With remote control	No
	Mounting method	Wall surface mounted / ceiling surface mounting
	With pictogram	No
	With light source	Yes
	Material housing	Aluminium die-cast
	Colour housing	White
	IP rating	IP20
PHOTOMETRIC	**Lamp type**	LED not exchangeable
	Photometric classification (C0)	D16
	Photometric classification	D16
DIMENSIONS	**Width**	167 mm
	Height/depth	142 mm
	Length	288 mm
CERTIFICATES/APPROVALS	**Compliant to AS/NZS CISPR 15**	Yes
	Compliant to AS/NZS 2293.3:2018	Yes
	Compliant to AS/NZS 60598.1:2017	Yes
	Compliant to AS/NZS 60598.2.22:2005	Yes

Published on 17 April 2026