ISO480MYS

Socomec ISO Enclosed Isolator, IP 65 Aluminium Yellow, Handle - Red, 4P 80A

ENCLOSED ISOLATORS



Component type	Switch disconnector
Range	ISO
Model	N/A
Product status	Existing

The Socomec ISO enclosed isolators deliver IP65, wall mountable, switching solutions ensuring coverage for any application. With a choice of plastic, aluminium and 316 stainless steel enclosures ranging from 25A to 250A, the range suits all environments. All handles allow for up to 3 padlocks in the OFF position and enclosure interlocking when in the ON position.

ELECTRICAL	Rated operating voltage Ue	400-690 V
	Rated uninterrupted current Iu	80 A
	Number of poles	4
	Frequency	50/60 Hz
	Rated operation current Ie at AC-23a, 690 V	80 A
	Rated short-time withstand current Icw	3 kA
	Rated impulse withstand voltage Uimp	6 kV
	Type of electrical connection of main circuit	Screw connection
	Rated operating voltage	690 V
	Number of auxiliary contacts as normally closed contact	0
	Number of auxiliary contacts as normally open contact	0
	Number of auxiliary contacts as change-over contact	0
	Motor drive integrated	No
CONSTRUCTION	Colour control element	Red
	Degree of protection (IP), front side	IP65
	Degree of protection (NEMA)	4X
	Version as reversing switch	No
	Number of switches	1
	Interlockable	No
MECHANICAL	Padlock locking	Yes
DIMENSIONS	Height	298 mm
	Width	200 mm
	Depth	124 mm

Published on 30 October 2026

ISO480MYS

Socomec ISO Enclosed Isolator, IP 65 Aluminium Yellow, Handle - Red, 4P 80A

ENCLOSED ISOLATORS

DIMENSIONS

Weight	0.33 kg
Connectable conductor cross section	2.5-35 mm²

RELATED PRODUCTS

ACCESSORY



Item No: 22001001
Required: No
Description: Socomec SLBM Fourth Pole Module - Switched, 20A



Item No: 22001004
Required: No
Description: Socomec SLBM Fourth Pole Module - Switched, 40A



Item No: 22001006
Required: No
Description: Socomec SLBM Fourth Pole Module - Switched, 63A



Item No: 22001008
Required: No
Description: Socomec SLBM Fourth Pole Module - Switched, 80A



Item No: 22001010
Required: No
Description: Socomec SLBM Fourth Pole Module - Switched, 100A

Item No: 22941005
Required: No
Description: Socomec SCOM/SLBM Terminal Shroud 1P, suits 16 - 40A (QTY 2)



Item No: 22943005
Required: No
Description: Socomec SCOM/SLBM Terminal Shroud 3P, suits 16 - 40A (QTY 2)



Item No: 22990001
Required: No
Description: Socomec SLBM Auxiliary Contact, 1 N.O + 1 N.C



Item No: 22990011
Required: No
Description: Socomec SLBM Auxiliary Contact, 2 N.O



Item No: 26990031
Required: No
Description: Socomec SLB Auxiliary Contact, 1 C.O, suits 1st Position 125 - 3200A



Item No: 26990032
Required: No
Description: Socomec SLB Auxiliary Contact, 1 C.O, suits 2st Position 125 - 3200A



Item No: NB160000
Required: No
Description: Socomec ISO Neutral Pole - Unswitched (Solid), suits 160A



Item No: NB250000
Required: No
Description: Socomec ISO Neutral Pole - Unswitched (Solid), suits 250A

Published on 30 October 2026