5034IRT4I

Allen-Bradley PointMax 4-Channel Analogue Input Module RTD/ Thermocouple Isolated

IN CABINET DISTRIBUTED IO



Component type	Fieldbus, decentr. periphery - analogue/digital I/O module
Range	PointMax
Model	N/A
Product status	Existing

The PointMax™ I/O platform enables you to adapt to modern industrial needs. It offers an extensive range of standard, safety, and specialty I/O modules and supports multiple network architectures and topology options. This remote I/O solution is ideal for discrete, hybrid, and process applications in multiple industries.

ELECTRICAL	Type of voltage (input voltage)	DC
	Type of output voltage	DC
	Number of channels	4
	Analogue input, thermocouple	Yes
	Resolution of the analogue inputs	16 Bit
	Analogue input signal configurable	Yes
	Permitted voltage at input	10-28.8 V
	Supply voltage DC	24-24 V
	Analogue inputs configurable	Yes
	Temperature measurement RTD	Yes
CONSTRUCTION	Suitable for safety functions	No
	Number of analogue inputs	4
	IP rating	IP20
DIMENSIONS	Width	15 mm
	Height	123.6 mm
	Depth	66.4 mm
ENVIRONMENT	Operating temperature	-20…60 °C
	Storage temperature	-40…85 °C
	Max. ambient humidity (non-condensing)	95 %

Published on 03 November 2026